
Declaration of Properties







Unique product type identification code

Identifier	A			В	C	D	and the same	E	AND THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED		
BIO CLEANER	4	15	35	no marking (circular)	no marking	no marking	BASIC	BASIC DUO	no marking (no phospsorus precipitation)		
BC*	6	16	40	K (rectangular)	PE	with a lid	OPTIMA	OPTIMA DUO	P-LESS (with phosphor precipitation)		
	8	20	45		PP	with an attachment	COMFORT	COMFORT DUO			
	10	25	50	A STATE OF THE PARTY OF THE PAR	SL	N (not self-supporting)	EXCLUSIVE	EXCLUSIVE DUO			
	12	30	CEAC 3	10 - A 1960	В		EXCLUSIVE UV	EXCLUSIVE UV DUO			

- * according to the specified identifier
- 2. Type, series or serial number or any other element identifying construction products according to Art. 11, Section 4: Serial Number: see the number of the Declaration
- Intended use or intended uses of the construction product in compliance with the relevant harmonized technical specification according to the qualification of the **Producer:** Biological Activation Wastewater Treatment Plant
- Name, business or registered trademark and contact address of the Producer according to Art. 11, Section 5:

ENVI-PUR, s.r.o., Na Vicovce 13/4, 160 00 Prague 6 - Dejvice, Czech Republic

- Name and contact address of an authorized representative with power of attorney related to the tasks specified in Art. 12, Section 2: ENVI-PUR Belgorod
- System or systems of assessing and verifying the stability of the properties of construction products as specified in Annex V: 3
- In case of a declaration of properties regarding a construction product which the harmonized standard applies to:

The Prague Technical and Testing Institute for Construction, Notified Body No. 1020, Prosecka 76, Prague 9, company identification code: 00015679, executed an initial test of the product type according to System 3 and issued a Properties Assessment Report No. 1020 - CPR - 090038112.

- In case of a declaration of properties regarding a construction product which a European technical assessment has been issued for: -
- 9. Properties specified in the Declaration

Basic Characteristics	Property	BASIC, OPTIMA, COMFORT	BASIC DUO, OPTIMA DUO, COMFORT DUO	BASIC P-LESS, OPTIMA P- LESS, COMFORT P- LESS	EXCLUSIVE P-LESS	BASIC DUO P- LESS, OPTIMA DUO P-LESS, COMFORT DUO P-LESS	EXCLUSIVE DUO P- LESS	EXCLUSIVE UV P-LESS	EXCLUSIVE UV DUO P- LESS	Harmonized Technical Specifications	
	COD (mg/l)	92%	94%	96 % 4)	95 % 4)	97 % 4)	96 % 4)	95 % 4)	96 % 4)	EN 12566-3 + A2:2013	
Purification efficiency degree	BOD _s (mg/l)	98%	99%	98 % 4)	98 % 4)	99 % 4)	98 % 4)	98 % 4)	98 % 4)		
	SS (mg/l)	96%	97%	97 % 4)	95 % 4)	98 % 4)	94 % 4)	95 % 4)	94 % 4)		
	N-NH ₄ ' (mg/l) 11)	77%	96%	71 % 4)	73 % ⁴⁾	80 % 4)	81 % 4)	73 % 4)	81 % 4)		
	N _{total} (mg/l) 3) 12)		51%	64 % ⁴⁾	64 % ⁴⁾	59 % 4)	59 % 4)	64 % 4)	59 % 4)		
	P _{total} (mg/l) ¹³⁾		19% 12)	94 % 4)	91 % 4)	95 % 4)	90 % 4)	91 % 4)	90 % 4)		
	Enteroccod (4)							99,99 %	100 %		
	Escherichia coli 14)		2	100				99,99 %	100 %		
	Fecal coliform bacteria 14)			ME -				99,99 %	100 %		
	Coliform bacteria 14)				10 · A:			99,99 %	100 %	- Vilginia	
	Somatic coliphage 14)			A TAKEN			d. A	100 %	100 %		
Rated organic daily load	0.24 / 0.36 / 0.48 / 0.60 / 0.72 / 0.90 / 0.96 / 1.20 / 1.80 / 2.10 / 2.40 / 2.70 / 3.00 kg BSK _s /day ⁶ l										
Rated daily flow	0.6 / 0.9 / 1.2 / 1.5 / 1.8 / 2.25 / 2.4 / 3.0 / 3.75 / 4.5 / 5.25 / 6.0 / 6.75 / 7.5 m³/day ⁶⁾										
Water tightness	Passed the water test										
Holding capacity	Passed the calculation for load by hydrostatic pressure, soil (1850 kg/m³; 36°), DRY / load by hydrostatic pressure, soil (1850 kg/m³; 36°), DRY / load by hydrostatic pressure, soil (1800 kg/m³; 42°), lids (2.5 kN/m²), DRY / load by hydrostatic pressure, soil (1800 kg/m³; 36°), lids (2.5 kN/m²), DRY / NPD / NPD / load by hydrostatic pressure, soil (1800 kg/m³; 36°), lids (2.5 kN/m²), DRY / NPD / NPD / NPD / load by hydrostatic pressure, soil (1850 kg/m³; 36°), lids (2.5 kN/m²), DRY / NPD										
Durability	Passed the test for PP / PE / stainless steel/concrete ⁸⁾										
Fire resistance	F										
Effect of dangerous substances	NPD										

- Comment: the values mentioned in "Declaration of properties", are achieved according to the EN 12566-3+A2
- 1) EP = equivalent person is defined pollution value 60 g BOD₅ per day and waste water value 150 I/day
- 2) WWTP rated polluting mater and hydraulic load must not be exceeded
- 3) initial load N_{total} max. 11 g/person*d
- 4) average value from all measured values5) geometric mean

- 6) according to Identifier A for 4 / 6 / 8 / 10 / 12 / 15 / 16 / 20 / 25 / 30 / 35 / 40 / 45 / 50
 7) according to Identifier A for 4 / A+C pro 6, 8, 10, 12, 16 PP / A+C+D for 4, 6, 8, 12, 15 PE with an attachment / A+B+C+D for 25, 30, 40, 50 K PP / A+B+C+D for 16, 20, 25, 30, 40, 50 K PP N (not self-supporting) / A+C for 16, 20, 25, 30, 35 40, 45, 50 PP N (not self-supporting) / C for SL / C for B

1/1

- 8) according to Identifier A for 4 / C for PP / C for PE / C for SL / C for B
- water temperature on the outlet is not under 12°C
 T_{min} = 3,4°C; T_{max} = 19,8°C
 with P-LESS (phosphorus precipitation)

- 14) with UV disinfection of purified waste water

Na Vičovce 13/4, 160 00 Praha

Provozovna Wilsonova 420, 392 (11 S.) Tel.: 381 203 256, fax: 2.5

10. The product property specified in Item 1 and 2 is in accordance with the property specified in Item 9.

This Declaration of Properties is issued at the sole responsibility of the Producer specified in Item 4.

Signed for and on behalf of the Producer:

In Soběslav on 1. 4. 2020

Milan Drda

Executive and Technical Director



ENVI-PUR, s.r.o. Na Vičovce 13/4 CZ-160 00 Praha 6 Czech Republic

Reg. no: 251 66 077 9 VAT no: CZ25166077 File number 167596C, registered in the Commercial Register at the Municipal Court in Prague

Head office & Production Wilsonova 420 CZ-392 01 Soběslav Czech Republic

+420 381 203 211

info@envi-pur.cz

www.envi-pur.cz